Baxter

HSCRIBE HOLTER ANALYSIS SYSTEM

PRODUCT FEATURES

SCALABLE SOLUTIONS

The **HScribe** Holter Analysis System enables flexible system configurations to satisfy a full range of Holter monitoring needs, from simple to complex installations. Multiple **HScribe** workstations can acquire and review Holter data, and generate Holter reports within a shared database. Customizable, electronic final reports can be manually or automatically exported to any networked destination.

MULTIPLE SCANNING OPTIONS

Retrospective, prospective and superimposition scanning modes with automatic Holter ECG strip selection are supported to enable both traditional and advanced scanning options.

ADVANCED VERITAS SIGNAL PROCESSING

The **VERITAS** signal processing algorithm, designed by **Mortara**, provides superior accuracy in beat detection, labeling and noise rejection, resulting in improved identification of events and rapid analysis of recordings.

PATIENT MONITORING DATA ACQUISITION

12-lead ECG monitored at a **Surveyor** Central System can be imported at the **HScribe** system, providing complete Holter analysis.

HL7 (HEALTH LEVEL 7) AND DICOM BIDIRECTIONAL INTERFACES

Receive demographics and orders from your HIS and export results to your EMR system with a custom **HL7** interface. Retrieve modality worklists and store final reports in your PACS with **DICOM**.

WEB-BASED HOLTER DATA IMPORT

The web upload feature enables Holter recording import from an unlimited number of remote client sites. A wizard-like application installed on your client's PC allows recorder preparation, local data download, patient demographic entry, diary event annotation and recording transfer to your facility via secure Internet/ Intranet connection.





Baxter

FEATURE	SPECIFICATION
Processor	Performance equivalent to an Intel Core i3
Graphics	1280 x 1024 (1920 x 1080 recommended)
RAM	4 GB
Operating System	Microsoft Windows 10 Professional or Microsoft Windows 11 Professional
Hard Drive Capacity	160 GB
Archive	Network or external USB drive
Input Devices	Standard keyboard and 2-button scroll mouse
Software Installation	CD-ROM
Device Classification	Type CF defibrillator-proof applied parts, internally powered
Network	100 Mbps connection or better
Printing Device	HP PCL5-compatible printer series (recommended)
USB Ports	2 free USB 2.0 ports

FEATURE	SERVER MINIMUM SPECIFICATION*
Processor	Performance equivalent to an Intel Xeon class, quad-core with hyperthreading
Graphics	1024 x 768
RAM	4 GB (8 GB recommended)
Operating System	Microsoft Windows 2016 and 2019 servers
System Disk	100 GB for OS and product installation (RAID recommended for data redundancy)
Data Disks	550 GB hard drive space available HD controller with 128 MB read/write cache (RAID recommended for data redundancy)
Archive	Network or external USB drive
Software Installation	CD-ROM
Network	100 Mbps connection or better
Input Devices	Standard keyboard and mouse

*Specifications subject to change without notice.

Contact your Baxter representative or scan the QR code to learn more.



Hillrom.com | Baxter International Inc.

Baxter, Hscribe, Mortara and Surveyor are trademarks of Baxter International Inc. or its subsidiaries.

DICOM is a trademark of the National Electrical Manufacturers Association. HL7 is a trademark of Health Level Seven, Inc. Intel, Intel Core, and Xeon are trademarks of Intel Corp. Windows is a trademark of Microsoft Corporation.

US-FLC90-230001 V1 04/23